

alan
conisbee
and associates

**consulting
structural
engineers**

1-5 Offord Street London N1 1DH

tel: 020 7700 6666

fax: 020 7700 6686

email: design@conisbee.co.uk

web: www.conisbee.co.uk

**STRUCTURAL APPRAISAL REPORT
FOR INSTALLATION OF WIND TURBINE AT
222 UPPER STREET,
LONDON N1.**

Ref: 060493

By: HMM

Date: NOV 2006

28531



INVESTOR IN PEOPLE

Alan Conisbee and Associates is a trading name of
Alan Conisbee and Associates Limited
Registered in England No 3958459

18982

directors:

Alan Conisbee BA BAI CEng MStructE
Chris Boydell BSc CEng MICE MStructE
Tim Attwood BSc CEng MStructE
Bob Stagg BSc CEng FStructE MICE
Thomas Beaven BEng CEng MStructE

associates:

Derek Crous MSc ZND (Hons) CEng MStructE
Tim Sheath BEng (Hons) CEng MStructE
Allan Dunsmore BEng CEng MICE MStructE
Isaac Hudson MEng MA(Cantab) CEng MStructE

consultants:

Martin Hargreaves MSc CEng MICE MStructE
David Bravery CEng FStructE

Structural Inspection Report

Job No.: 060493 **Date:** 6th December 2006

Property Address: 222 Upper Street, Islington. N1

Client Contact: Graham Lowe, Energy Conservation officer, Islington Council.

Client Brief: To report on the feasibility of the existing roof structure to provide support for a wind turbine (details of which have been provided), and to provide a design of a suitable base for the mast for costing purposes. Information provided by Proven, the mast and turbine's manufacturer and designer, which has been used for this report, is included in Appendix A.

Observations:

The following information was obtained during two site visits on the 7th and 20th November, 2006 and viewing record drawings of 222 Upper Street at Islington's Building Control on 20th November, of which some copies were taken of reinforcement drawings.

1. The roof is a fairly uninterrupted flat roof, with an existing designated area for plant. There are some rain water pipe inlets and air vents.
2. We understand it is planned to re-asphalt the roof in the near future, so that any bases for the proposed wind turbine system maybe incorporated into the roof structure and suitably weather proofed at this time with without much further cost involved. Present items on the roof viewed do not puncture the asphalt.
3. The building structure is of reinforced concrete, with perimeter columns and a few internal columns supporting reinforced concrete floor slabs. The roof slab is 250mm thick reinforced concrete.
4. Reinforcement plans of the building, including the roof ('Block B') were found at Islington's Building Control; however whilst these provide guidance it is possible they are not exactly as built.
5. The present plant is located on a grillage which secured to the roof by concrete blocks, there do not seem to be any positive fixings through to the r.c.slab. No details of this were available at Building Control.
6. Other items, such as an aerial, have been held down with concrete blocks on the support brackets, with no visible connection to the roof.
7. Existing photographs of the roof are attached.
8. Presently there is no balustrade around the perimeter of this portion of the roof.
9. In conversation with David Watson at Proven Energy, it is understood that the winch to lower the mast for maintenance approximately twice a year is not a permanent fixture and needs no fixing. The winch, at approx 1000mmx300mm has enough self-dead weight to counteract the forces induced by the lifting and lowering of the mast and mast head.

Conclusions & Suggested Works:

1. A wind turbine mast and winch may be structurally supported by this building.
2. The reinforced concrete roof is a sufficient supporting structure for the mast base with support detail provided; which deepens the depth of the slab in an isolated area to allow the slab to take and spread the over-turning moments provided.
3. A layout has been chosen that provides 2.5m clear space around the mast head, when laid flat, so that the turbine unit may rest on to the roof slab with sufficient room for maintenance to take place as required.
4. It is proposed to increase the depth of the slab locally to support the winch and mast base. This will provide a greater depth for embedment of bolts. The existing reinforced concrete surface will need to be scored or roughened with high pressure water jets to achieve a suitable bonding of the new concrete overlay. Refer to Drawings 02 & 03.
5. The vibrations from the wind turbine are assumed to be negligible, and by experience may be dealt with in one of two ways:
 - a. Introduction of a 'damper' system into the connection of the mast into the roof, either dampening units or rubber washers;
 - b. The vibrations being dampened by the dead weight of the supporting structure;

In this case, we consider that the reinforced concrete framed building has sufficient dead-load and stiffness to dampen any vibrations incurred via the mast.

6. Steel bases plates to the mast may then be bolted through the new concrete pads and into the existing reinforced concrete slab.
7. The winch itself does not need any fixing into the roof, as it is self-weighted and is bought in as maintenance is required. The proposed location of the winch is indicated on Drawings 01 & 02. Whilst the weight of the winching unit is unknown, the existing reinforced concrete slab has been checked, and is sufficient to take a winch and loads induced as necessary.
8. As the winch will be bought into the position whenever maintenance is required, a suitable path, or surface should be provided over which the winch may be run and to locate it on to protect the (new) weather protection layer.
9. To satisfy working-at-height Health & Safety for the erection and maintenance of the mast, a balustrade or safety system may be required. This should be considered at this stage to be included in the works if necessary.
10. It is important that the area where the works to the new reinforced concrete base are to take place are scanned to check and record existing reinforcement in the top of the slab and to enable existing reinforcement to be avoided.

Photographs.





Photo 1: View South-West



Photo 2: View south, taken from foot path next to plant area (not seen).

DRAWINGS AND DETAILS OF PROPOSED BASE DESIGN.



OUTLINE OF EXISTING
LED THE R.C. SLAB &
UPSTAND.

MARKED UP PLAN OF ROOF
TO SHOW PROPOSED LOCATION
OF MAST & WINCH.



: R.C. STRUCTURE BELOW.

alan
conisbee
and associates

consulting
structural
engineers

1-5 Offord Street London N1 1DH
tel 020 7700 6666 e-mail design@conisbee.
fax 020 7700 6686 web www.conisbee.

project	WIND TURBINE: 222 UPPER STREET.	job no.	0604 93
title	MARKED UP PLAN TO SHOW BASE LOCATIONS.	drg. no.	01
		scale	1:100
		date	DEC 06
		drawn	HMM
		checked	



INDICATES EXISTING/PROPOSED AREA/WALKWAY TO BE SUITABLE FOR WINCH MOVEMENT



INDICATES AREA FOR WINCH

SITE BOUNDARY

alan
conisbee
and associates
consulting structural engineers
1-5 Offord Street London N1 1DH
tel 020 7700 6666 e-mail design@conisbee.co.uk
fax 020 7700 6686 web www.conisbee.co.uk

REV A. CHANGES MADE. *HMH*

project	WIND TURBINE	job no.	060493
	-222 UPPER STREET.	drg. no.	02
title	PLAN TO SHOW MAST BASE & SURFACE LOCATIONS.	scale	1:100
		date	DEC 06.
		drawn	HMH
		checked	

alan
conisbee
and associates

1-5 Offord Street London N1 1DH

tel 020 7700 6666

fax 020 7700 6686

email design@conisbee.co.uk

web www.conisbee.co.uk

consulting
structural
engineers

project

WIND TURBINE.

222 UPPER STREET.

title

BASE DETAIL - MAST.
PLAN.

job no.

000497

drg. no.

03

scale 1:10


date 5-12-06

drawn G.M.H.

checked

rev. A date 13/12/06 CHANGE MADE G.M.H.

EXISTING 250 THK R.C. SLAB - PREPARED FOR NEW R.C. TOP PAD: ROUGHENED
WITH HIGH PRESSURE WATER OR SCORED. PRIMED WITH GROUT ON 24 HR WETTED SURFACE
TO RELIEVE NEW CONCRETE.



2000 SQ R.C. PAD, 200mm THICK
DOWN TO EXISTING ROOF
SCHED. U-BARS RESIN ANCHORED
INTO EXISTING R.C. WITH MIN
150mm EMBEDMENT DEPTH AVOID
EXISTING REINFORCEMENT. U-BARS
AT 200/400 mm C/C. 10mm DIA
T25@150 C/C IN TOP, BOTH DIRECTIONS
IN TOP & BOTTOM OF NEW 200mm
CONE, THREADED THROUGH U-BARS (SPACE FOR GROUT). NOTES: REFER TO DRAWING 03.

*1000mm DIA, 20mm THK STEEL PLATE
(GALVANIZED OR STAINLESS STEEL),
BOLTED TO NEW & EXISTING R.C.
WITH MIN 10 NO M20 HSA-P
MULTI ANCHORS. ALLOW FOR
25mm WORKING SPACE GROUT.
SUITABLE WELDERS TO BE USED TO
AVOID BI-METALLIC CORROSION IF
DIFFERENT MATERIALS USED.

alan
conisbee
and associates

1-5 Offord Street London N1 1DH

tel 020 7700 6666

fax 020 7700 6686

email design@conisbee.co.uk

web www.conisbee.co.uk

consulting
structural
engineers

project

WIND TURBINE -
222 VIKER STREET, N1

job no.

060497

drg. no.

04

title

BASE DETAIL - MAST
SECTION


scale 1:10

date 5-12-06

drawn H.M.H.

checked

rev. A date 13/12/06 CHANGES MADE H.M.H.



NOTES

- DO NOT DIMENSION FROM THIS DRAWING.
- THIS DRAWING IS FOR COSTING ONLY
- CONCRETE GRADE C35
- ALL STEEL TO BE STAINLESS OR GALVANIZED GRADE S275.
- ALL REINFORCEMENT TO BE HIGH YIELD.
- COVER TO REINFORCEMENT 40 mm.
- * SIZE OF STEEL PLATE & LOCATION & SIZE OF RECEIVING BOLTS TO BE
AGREED WITH FOUNDATION ENGINEER. ALSO DETAIL OF HINGE.

APPENDIX A

INFORMATION PROVIDED ON 6KW TURBINE USED FOR CALCULATIONS

Turbine Foundation Loads **Anchor Point Loading During Winching** **Proven Energy WT 6000 Wind Turbine TM900**


Revision			Prepared by	
Status	Date	No.	Author	Checked
Issued	20/03/05	10.1	NJH	JA



Input Parameters

Head Mass = 500 kg = 5.0 kN
 Mast Mass = 300 kg = 3.0 kN
 Mast Length = 9 m
 Mast CoG = 3.9 m
 Gin pole length = 3 m
 Win Winching distance = 7 - 9 m

 Gin Pole angle = 82 deg
 1.4 rads
 Winch cable angle = 19 deg
 0.3 rads



Find the lifting moment required due to the head weight and tower weight

Assume highest loading is when the turbine is horizontal, and has just left the ground, this causes the greatest moment,

Total moment due to head and mast weight = 57.5 kNm
 Horizontal force at the end of the gin pole = 19.5 kN

Winch Cable tension = 20.4 kN

Winch Anchor X = 19.5 kN

Winch Anchor Y = 6.2 kN

References

- 1. From Technical Specifications pdf on Proven Website
- 2. From SE model

Turbine Foundation Loads

Wind Thrust Overturning Moment

Proven Energy WT 6000 Wind Turbine TM900

Revision			Prepared by	
Status	Date	No.	Author	Checked
Issued	18/05/06	0.1	NJH	JA



Calculate the Tower foundation loads due the wind loading on the turbine loads in accordance with international norm: IEC 61400-2
Assume that the tower wind loading is a uniformly distributed load, variations in wind speed with height will be neglected in this calculation.


Input Parameters

Head Mass = 500 kg
Mast Mass = 360 kg
Mast Length = 9 m
Head Thrust = 10 kN
Tower Thrust = 7.7 kN

Total Overturning Moment = 118.9 kNm
Total Horizontal Thrust = 17.7 kN
Turbine Weight = 8.4 kN (vertical force ex. foundation)

References

- 1. From Technical Specifications pdf on Proven Website
- 2. From Tower wind loading calculations spreadsheet




APPENDIX B

ANALYSIS OF REINFORCED CONCRETE ROOF FOR EXISING AND PROPOSED CONDITIONS


View - MXX- (W&A) Cases:

6 (Existing Slab ULS)




View - MYY- (W&A) Cases: 6 (Existing Slab ULS)

Cases: 6 (Existing Slab ULS)




View - MXX+ (W&A) Cases: 6 (Existing Slab ULS)

Cases: 6 (Existing Slab ULS)



View - MYY+ (W&A) Cases: 6 (Existing Slab ULS)



Cases: 6 (Existing Slab ULS)

alan conisbee and associates consulting structural engineers 1-5 Offord Street London N1 1DH tel 020 7700 6666 fax 020 7700 6666 email tec@conisbee.co.uk web www.conisbee.co.uk		project WIND TURBINE 222 UPPER STREET	job no. 060493
		title Existing Roof Floor Slab Bottom Mxx N-S REINFORCEMENT	sheet no. date 14.12.2006 engineer MG checked
rev	date		

BS 8007 Table 3.1	Material Properties			
	Concrete strength	f_{cu}	30 N/mm ²	
	Reinforcement strength	f_y	460 N/mm ²	$= 130 \text{ N/mm}^2 \times 1.45 \text{ fcs}$
	Slab dimensions			
	Overall thickness	h	250 mm	
	Breadth	b	1000 mm /m width	
	Cover		43 mm	
	Effective depth	d	207 mm	$= h - \text{cover}$
				$d = 207 \text{ mm}$
		Forces (ultimate)		
Maximum applied moment	M	40.0 kNm /m width		$M = 40.0 \text{ kNm/m}$
Maximum applied shear	F	18.0 kN /m width		$F = 18.0 \text{ kN/m}$
Ultimate moment capacity	M_u	201 kNm /m width	$= 0.156 f_{cu} b d^2$	$M_u = 201 \text{ kNm/m}$
1 Design as singly reinforced beam.				
Design as singly reinforced beam.				
Tension Reinforcement				
Factor	K	0.031	$= M / f_{cu} b d^2$	$K = 0.0311$
Lever arm factor	z	197 mm	$= d (0.5 + \sqrt{0.25 - K / 0.9})$	$z = 197 \text{ mm}$
Neutral axis depth factor	x	23 mm	$= (d - z) / 0.45$	$x = 23 \text{ mm}$
Minimum area of steel	$A_{s,min}$	325 mm ² /m width	$= 0.0013 b h$	
Area of steel required	A_s	465 mm ² /m width	$= M / 0.95 f_y z$	$A_{s,req} = 465.46 \text{ mm}^2/\text{m}$
Tension Reinforcement Provided				
Bar diameter	ϕ'	12 mm		
Bar spacing		200 mm centers		OK EXISTING RFMT T12'S@150C/C
Area provided	$A_{s,prov}$	565 mm ² /m width		
Bar diameter	ϕ'	0 mm		
Number of bars	No.	200 mm centers		
Area provided	$A_{s,prov}$	0 mm ² /m width		
Total area provided	$A'_{s,prov}$	565.5 mm ² /m width	OK	$A_{s,prov} = 565.49 \text{ mm}^2/\text{m}$
Shear Strength				
Shear stress	v	0.09 N/mm ²		
Shear stress limits		5.00 N/mm ² OK		
		4.38 N/mm ² OK		
Factor	R	0.273		
Design concrete shear stress	v_c	0.514 N/mm ² 1		
Provide minimum links				

alan conisbee and associates consulting structural engineers 1-5 Offord Street London N1 1DH tel 020 7700 6666 fax 020 7700 6686 email tec@conisbee.co.uk web www.conisbee.co.uk		project WIND TURBINE 222 UPPER STREET	job no. 060493
		title Existing Roof Floor Slab Bottom Myy (E-W)	sheet no.
			date 14.12.2006
			engineer MG
			checked
rev	date		

BS 8007 Table 3.1	Material Properties				
	Concrete strength	f_{cu}	30 N/mm ²		
	Reinforcement strength	f_y	460 N/mm ²	$= 130 \text{ N/mm}^2 \times 1.45 \text{ fogs}$	
	Slab dimensions				
	Overall thickness	h	250 mm		
	Breadth	b	1000 mm /m width		
	Cover		31 mm		
	Effective depth	d	219 mm	$= h - \text{cover}$	$d = 219 \text{ mm}$
	Forces (ultimate)				
	Maximum applied moment	M	55.0 kNm /m width		$M = 55.0 \text{ kNm/m}$
	Maximum applied shear	F	18.0 kN /m width		$F = 18.0 \text{ kN/m}$
	Ultimate moment capacity	M_u	224 kNm /m width	$= 0.156 f_{cu} b d^2$	$M_u = 224 \text{ kNm/m}$
	1 Design as singly reinforced beam.				
	Design as singly reinforced beam.				
	Tension Reinforcement				
Factor	K	0.038	$= M / f_{cu} b d^2$	$K = 0.0382$	
Lever arm factor	z	208 mm	$= d (0.5 + \sqrt{0.25 - K / 0.9})$	$z = 208 \text{ mm}$	
Neutral axis depth factor	x	24.33 mm	$= (d - z) / 0.45$	$x = 24 \text{ mm}$	
Minimum area of steel	$A_{s,min}$	325 mm ² /m width	$= 0.0013 b h$		
Area of steel required	A_s	605 mm ² /m width	$= M / 0.95 f_y z$	$A_{s,req} = 604.94 \text{ mm}^2/\text{m}$	
Tension Reinforcement Provided					
Bar diameter	ϕ'	12 mm			
Bar spacing		150 mm centers	OK EXISTING PROVIDED IS T12'S @150 C/C		
Area provided	$A_{s,prov}$	754 mm ² /m width			
Bar diameter	ϕ'	0 mm			
Number of bars	No.	200 mm centers			
Area provided	$A_{s,prov}$	0 mm ² /m width			
Total area provided	$A'_{s,prov}$	754 mm ² /m width	OK	$A_{s,prov} = 753.98 \text{ mm}^2/\text{m}$	
Shear Strength					
Shear stress	v	0.08 N/mm ²			
Shear stress limits		5.00 N/mm ² OK			
		4.38 N/mm ² OK			
Factor	R	0.344			
Design concrete shear stress	v_c	0.547 N/mm ² 1			
Provide minimum links					

alan
conisbee
and associates

consulting structural engineers
1-5 Offord Street London N1 1DH
tel 020 7700 6666 fax 020 7700 6686
email tec@conisbee.co.uk
web www.conisbee.co.uk

project
WIND TURBINE
222 UPPER STREET

job no.
060493

title
Proposed Roof Floor Slab
Bottom Mxx

sheet no.

date 14.12.2006

engineer
MG

checked

rev date

BS 8007
Table 3.1

Material Properties

Concrete strength f_{cu} 30 N/mm²

Reinforcement strength f_y 460 N/mm² = 130 N/mm² x 1.45 fcs

Slab dimensions

Overall thickness h 450 mm

Breadth b 1000 mm /m width

Cover 43 mm

Effective depth d 407 mm = $h - \text{cover}$ $d = 407 \text{ mm}$

Forces (ultimate)

Maximum applied moment M 111.0 kNm /m width $M = 111.0 \text{ kNm/m}$

Maximum applied shear F 18.0 kN /m width $F = 18.0 \text{ kN/m}$

Ultimate moment capacity M_u 775 kNm /m width = $0.156 f_{cu} b d^2$ $M_u = 775 \text{ kNm/m}$

† Design as singly reinforced beam.

Design as singly reinforced beam.

Tension Reinforcement

Factor K 0.022 = $M / f_{cu} b d^2$ $K = 0.0223$

Lever arm factor z 387 mm = $d (0.5 + \sqrt{0.25 - K / 0.9})$ $z = 387 \text{ mm}$

Neutral axis depth factor x 45.22 mm = $(d - z) / 0.45$ $x = 45 \text{ mm}$

Minimum area of steel $A_{s,min}$ 585 mm² /m width = $0.0013 b h$

Area of steel required A_s 657 mm² /m width = $M / 0.85 f_y z$ $A_{s,req} = 656.94 \text{ mm}^2/\text{m}$

Tension Reinforcement Provided

Bar diameter ϕ' 12 mm

Bar spacing 150 mm centers

Area provided $A_{s,prov}$ 754 mm² /m width **LESS THAN AS EXISTING**
+ ACTUALLY OVER 2 SQ M=OK

Bar diameter ϕ' 0 mm

Number of bars N_o 200 mm centers

Area provided $A_{s,prov}$ 0 mm² /m width

Total area provided $A'_{s,prov}$ 754 mm² /m width **OK** $A_{s,prov} = 753.98 \text{ mm}^2/\text{m}$

Shear Strength

Shear stress v 0.04 N/mm²

Shear stress limits 5.00 N/mm² OK
4.38 N/mm² OK

Factor R 0.185

Design concrete shear stress v_c 0.383 N/mm² †

Provide minimum links

alan conisbee <i>and associates</i> consulting structural engineers 1-5 Offord Street London N1 1DH tel 020 7700 6666 fax 020 7700 6686 email tec@conisbee.co.uk web www.conisbee.co.uk		project WIND TURBINE 222 UPPER STREET	job no. 060493
		title Proposed Roof Floor Slab Bottom Mxx	sheet no. date 14.12.2006 engineer MG checked
rev	date		

BS 8007 Table 3.1	Material Properties				
	Concrete strength	f_{cu}	30 N/mm ²		
	Reinforcement strength	f_y	460 N/mm ²	$= 130 \text{ N/mm}^2 \times 1.45 \text{ fcs}$	
	Slab dimensions				
	Overall thickness	h	450 mm		
	Breadth	b	1000 mm /m width		
	Cover		43 mm		
	Effective depth	d	407 mm	$= h - \text{cover}$	$d = 407 \text{ mm}$
	Forces (ultimate)				
	Maximum applied moment	M	111.0 kNm /m width		$M = 111.0 \text{ kNm/m}$
	Maximum applied shear	F	18.0 kN /m width		$F = 18.0 \text{ kN/m}$
	Ultimate moment capacity	M_u	775 kNm /m width	$= 0.156 f_{cu} b d^2$	$M_u = 775 \text{ kNm/m}$
	1 Design as singly reinforced beam.				
	Design as singly reinforced beam.				
	Tension Reinforcement				
Factor	K	0.022	$= M / (f_{cu} b d^2)$	$K = 0.0223$	
Lever arm factor	z	387 mm	$= d (0.5 + \sqrt{0.25 - K / 0.9})$	$z = 387 \text{ mm}$	
Neutral axis depth factor	x	45.22 mm	$= (d - z) / 0.45$	$x = 45 \text{ mm}$	
Minimum area of steel	$A_{s,min}$	585 mm ² /m width	$= 0.0013 b h$		
Area of steel required	A_s	657 mm ² /m width	$= M / 0.95 f_y z$	$A_{s,req} = 656.94 \text{ mm}^2/\text{m}$	
Tension Reinforcement Provided					
Bar diameter	ϕ'	12 mm			
Bar spacing		150 mm centers			
Area provided	$A_{s,prov}$	754 mm ² /m width	LESS THAN AS EXISTING + ACTUALLY OVER 2 SQ M=OK		
Bar diameter	ϕ'	0 mm			
Number of bars	No.	200 mm centers			
Area provided	$A_{s,prov}$	0 mm ² /m width			
Total area provided	$A'_{s,prov}$	754 mm ² /m width	OK	$A_{s,prov} = 753.98 \text{ mm}^2/\text{m}$	
Shear Strength					
Shear stress	v	0.04 N/mm ²			
Shear stress limits		5.00 N/mm ² OK 4.38 N/mm ² OK			
Factor	R	0.185			
Design concrete shear stress	v_c	0.383 N/mm ² 1			
Provide minimum links					

alan conisbee <i>and associates</i> consulting structural engineers 1-5 Offord Street London N1 1DH tel 020 7700 6666 fax 020 7700 6686 email tec@conisbee.co.uk web www.conisbee.co.uk		project WIND TURBINE 222 UPPER STREET	job no. 060493
		title Proposed Roof Floor Slab Bottom Myy	sheet no. date 14.12.2006 engineer MG checked
rev	date		

BS 8007 Table 3.1	Material Properties				
	Concrete strength	f_{cu}	30 N/mm ²		
	Reinforcement strength	f_y	460 N/mm ²	$= 130 \text{ N/mm}^2 \times 1.45 \text{ fas}$	
	Slab dimensions				
	Overall thickness	h	450 mm		
	Breadth	b	1000 mm /m width		
	Cover		31 mm		
	Effective depth	d	419 mm	$= h - \text{cover}$	$d = 419 \text{ mm}$
	Forces (ultimate)				
	Maximum applied moment	M	90.0 kNm /m width		$M = 90.0 \text{ kNm/m}$
Maximum applied shear	F	18.0 kN /m width		$F = 18.0 \text{ kN/m}$	
Ultimate moment capacity	M_u	822 kNm /m width	$= 0.156 f_{cu} b d^2$	$M_u = 822 \text{ kNm/m}$	
1 Design as singly reinforced beam.					
Design as singly reinforced beam.					
Tension Reinforcement					
Factor	K	0.017	$= M / (f_{cu} b d^2)$	$K = 0.0171$	
Lever arm factor	z	398 mm	$= d \{ 0.5 + \sqrt{0.25 - K / 0.9} \}$	$z = 398 \text{ mm}$	
Neutral axis depth factor	x	46.56 mm	$= (d - z) / 0.45$	$x = 47 \text{ mm}$	
Minimum area of steel	$A_{s,min}$	585 mm ² /m width	$= 0.0013 b h$		
Area of steel required	A_s	585 mm ² /m width	$= M / 0.95 f_y z$	$A_{s,req} = 585 \text{ mm}^2/\text{m}$	
Tension Reinforcement Provided					
Bar diameter	ϕ'	12 mm			
Bar spacing		150 mm centers	AS EXISTING=OK		
Area provided	$A_{s,prov}$	754 mm ² /m width			
Bar diameter	ϕ'	0 mm			
Number of bars	No.	200 mm centers			
Area provided	$A_{s,prov}$	0 mm ² /m width			
Total area provided	$A'_{s,prov}$	754 mm ² /m width	OK	$A_{s,prov} = 753.99 \text{ mm}^2/\text{m}$	
Shear Strength					
Shear stress	v	0.04 N/mm ²			
Shear stress limits		5.00 N/mm ² OK			
		4.38 N/mm ² OK			
Factor	R	0.18			
Design concrete shear stress	v_c	0.379 N/mm ² 1			
Provide minimum links					


alan conisbee <i>and associates</i> consulting structural engineers 1-5 Offord Street London N1 1DH tel 020 7700 6666 fax 020 7700 6686 email tec@conisbee.co.uk web www.conisbee.co.uk		project WIND TURBINE 222 UPPER STREET	job no. 060493
		title Proposed Roof Floor Slab Top Mxx	sheet no. date 14.12.2006 engineer MG checked
rev	date		

BS 8007 Table 3.1	Material Properties				
	Concrete strength	f_{cu}	30 N/mm ²		
	Reinforcement strength	f_y	460 N/mm ²	$= 130 \text{ N/mm}^2 \times 1.45 \text{ fas}$	
	Slab dimensions				
	Overall thickness	h	450 mm		
	Breadth	b	1000 mm /m width		
	Cover		43 mm		
	Effective depth	d	407 mm	$= h - \text{cover}$	$d = 407 \text{ mm}$
	Forces (ultimate)				
	Maximum applied moment	M	50.0 kNm /m width		$M = 50.0 \text{ kNm/m}$
Maximum applied shear	F	18.0 kN /m width		$F = 18.0 \text{ kN/m}$	
Ultimate moment capacity	M_u	775 kNm /m width	$= 0.156 f_{cu} b d^2$	$M_u = 775 \text{ kNm/m}$	
† Design as singly reinforced beam.					
Design as singly reinforced beam.					
Tension Reinforcement					
Factor	K	0.01	$= M / f_{cu} b d^2$	$K = 0.0101$	
Lever arm factor	z	387 mm	$= d \{ 0.5 + \sqrt{0.25 - K / 0.9} \}$	$z = 387 \text{ mm}$	
Neutral axis depth factor	x	45.22 mm	$= (d - z) / 0.45$	$x = 45 \text{ mm}$	
Minimum area of steel	$A_{s,min}$	585 mm ² /m width	$= 0.0013 b h$		
Area of steel required	A_s	585 mm ² /m width	$= M / 0.95 f_y z$	$A_{s,req} = 585 \text{ mm}^2/\text{m}$	
Tension Reinforcement Provided					
Bar diameter	ϕ'	12 mm			
Bar spacing		150 mm centers	ACTUAL PROVIDED T12'S @200 OVER		
Area provided	$A_{s,prov}$	754 mm ² /m width	2m WIDTH, TOTAL=1132mm OR 566 OVER 1m.		
Bar diameter	ϕ'	0 mm			
Number of bars	No.	200 mm centers			
Area provided	$A_{s,prov}$	0 mm ² /m width			
Total area provided	$A'_{s,prov}$	754 mm ² /m width	OK	$A_{s,prov} = 753.98 \text{ mm}^2/\text{m}$	
Shear Strength					
Shear stress	v	0.04 N/mm ²			
Shear stress limits		5.00 N/mm ² OK			
		4.38 N/mm ² OK			
Factor	R	0.185			
Design concrete shear stress	v_c	0.383 N/mm ²			
Provide minimum links					

alan conisbee and associates consulting structural engineers 1-5 Offord Street London N1 1DH tel 020 7700 6666 fax 020 7700 6686 email tec@conisbee.co.uk web www.conisbee.co.uk		project WIND TURBINE 222 UPPER STREET	job no. 060493
rev date		title Proposed Roof Floor Slab Top Myy	sheet no. date 14.12.2006 engineer MG checked
BS 8007 Table 3.1 Material Properties Concrete strength f_{cu} 30 N/mm² Reinforcement strength f_y 460 N/mm² = 130 N/mm² x 1.45 <i>for</i> Slab dimensions Overall thickness h 450 mm Breadth b 1000 mm /m width Cover 31 mm Effective depth d 419 mm = $h - \text{cover}$ $d =$ 419 mm Forces (ultimate) Maximum applied moment M 32.0 kNm /m width $M =$ 32.0 kNm/m Maximum applied shear F 18.0 kN /m width $F =$ 18.0 kN/m Ultimate moment capacity M_u 822 kNm /m width = $0.156 f_{cu} b d^2$ $M_u =$ 822 kNm/m 1 Design as singly reinforced beam. Design as singly reinforced beam. Tension Reinforcement Factor K 0.006 = $M / f_{cu} b d^2$ $K =$ 0.0061 Lever arm factor z 398 mm = $d \{ 0.5 + \sqrt{0.25 - K / 0.9} \}$ $z =$ 398 mm Neutral axis depth factor x 46.56 mm = $(d - z) / 0.45$ $x =$ 47 mm Minimum area of steel $A_{s,min}$ 585 mm² /m width = $0.0013 b h$ Area of steel required A_s 585 mm² /m width = $M / 0.95 f_y z$ $A_{s,req} =$ 585 mm² /m Tension Reinforcement Provided Bar diameter ϕ' 12 mm Bar spacing 150 mm centers AS Mxx Area provided $A_{s,prov}$ 754 mm² /m width Bar diameter ϕ' 0 mm Number of bars $No.$ 200 mm centers Area provided $A_{s,prov}$ 0 mm² /m width Total area provided $A'_{s,prov}$ 754 mm² /m width OK $A_{s,prov} =$ 753.98 mm² /m Shear Strength Shear stress v 0.04 N/mm² Shear stress limits 5.00 N/mm² OK 4.38 N/mm² OK Factor R 0.18 Design concrete shear stress v_c 0.379 N/mm² 1 Provide minimum links			

APPENDIX C


SCAN OF EXSITING REINFORCMENT DRAWINGS





notes

- 1 Do not scale this drawing. Work from figured dimensions only.
- 2 No deviation from the details shown on this drawing is allowed without our prior permission in writing.
- 3 Read this drawing with all Architects and Service Engineers relevant details and our drg. nos.
4. Concrete should be grade 30 $\frac{1}{2}$ inch at 28 days.
5. Maximum aggregate size to be 70 mm
6. Unless noted cover to steel 70 mm
7. For location see Drgs. Nos. 1750/5/3
8. Bending schedule papers 01 - 00
9. A.P. Alternately Placed, N.F. Near Face, F.F. Far Face,
10. A.S. Alternately Staggered, A.R. Alternately Reversed,
11. T. Top, B. Bottom, LL = LONG LEG
12. FOR BEAM DETAILS SEE DRG No. 1750/5/1
13. **SL5** DENOTES SHEAR LINK DETAILS SEE DRG No. 1750/5/1

- 6. Y10.05.700 3 NF 3FF
- 70 cover to 57
- 65 Y12.50.150 U BARS LLT.
- 65 Y12.55.750 U BARS LLT.
- 24. Y10.54.700 T.
- 3. Y16.77.750 LLT.
- 65 Y12.57. + 64 Y12.53. APB.
- AT CRS SHOWN
- 1. Y10.00 U BAR LLT.
- 1. Y12.02 B.
- 30. Y10.50 + 30. Y10.51. AP 150 T.
- 7. Y10.40 + 7. Y10.40 AP 150 T.
- 2. Y10.75. 1 T. 18. 1 BARS
- 2. Y10.76. 700 LINKS.
- 2. Y12.05 B.
- 1. Y10.01 U BAR LLB.
- 4. Y17.00 U BARS
- 6 Y10.102.700 3 NF 3FF
- 131. Y16.47 AS T.
- AT CRS SHOWN







131 Y10.47 AS T,
AT CRS SHOWN

4 Y10.26 B₁ + 4 Y10.87 T₁

66 Y10.45 + 65 Y10.46 AP B₁
AT CRS SHOWN

6 Y10.102.700, 3NF 3FF

31 Y10.43 + 31 Y10.44 AP 150 T₁

74 Y10.42.700 T₁

132 Y10.41 U BARS 11T,
AT CRS SHOWN

55 Y10.11.250 U BARS

CAMPBELL BENTON & PARTNERS
DATE 6 SEP 1982
ISSUED

REV AMENDMENT

CRP CAMPBELL & PARTNERS
Chartered Civil and Structural Engineers

TUDOR HOUSE, 26 UPPER TEDDINGTON ROAD, HAMPTON
KINGSTON UPON THAMES, SURREY, KT1 4DY
62 BRAMHALL LANE SOUTH, STOCKPORT, SK7 2DU
41-43 GEORGE STREET, CROYDON, CRO 9YG
85-103 QUEENS ROAD, READING, RG1 4PT

Contract
MUNICIPAL OFFICES - ISLINGTON

architect
T. P. BENNETT & SON

**R.C. DETAILS OF ROOF SLAB
BLOCK B**

drawn LN checked
date 16.7.82 scale 1:50

Job no. 1750 Drg. no. R5/3

DISTRICT
- 7/SEP

